# **SAFETY DATA SHEET**

# **DIESEL/ BIODIESEL MIX**

Infosafe No.: LQ3RB ISSUED Date : 11/09/2019 ISSUED by: UNITED PETROLEUM PTY LTD

# **1. IDENTIFICATION**

GHS Product Identifier DIESEL/ BIODIESEL MIX

Company Name UNITED PETROLEUM PTY LTD

Address 600 Glenferrie Road Hawthorn Vic 3122 AUSTRALIA

**Telephone/Fax Number** Tel: (03)9413 1400 Fax: (03)9413 1401

Emergency phone number 1300 131 001

**Recommended use of the chemical and restrictions on use** Fuel.

# 2. HAZARD IDENTIFICATION

#### GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia. Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Flammable Liquids: Category 4 Acute Toxicity - Inhalation: Category 4 Carcinogenicity: Category 2 Aspiration Hazard: Category 1 Hazardous to the Aquatic Environment - Acute Hazard: Category 2 Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2 Signal Word (s)

DANGER

Hazard Statement (s)
AUH066 Repeated exposure may cause skin dryness or cracking.
H227 Combustible liquid.
H332 Harmful if inhaled.
H351 Suspected of causing cancer.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

#### Pictogram (s)

Exclamation mark, Health hazard, Environment



#### Precautionary statement – Prevention

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

#### **Precautionary statement – Response**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P370+P378 In case of fire: Use carbon dioxide, dry chemical, foam, water spray for extinction. P391 Collect spillage.

#### **Precautionary statement – Storage**

P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

#### **Precautionary statement – Disposal**

P501 Dispose of contents/container to an approved waste disposal plant.

#### **Other Information**

This product contains an Ototoxic substance.

Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### Ingredients

Name	CAS	Proportion
Fuel, diesel No. 2	68476-34-6	60-95 %
Methyl Esters	67784-80-9	5-40 %
Ingredients determined not to be hazardous		Balance

# **4. FIRST-AID MEASURES**

# Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

#### Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

#### Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

#### Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

#### **First Aid Facilities**

Eyewash, safety shower and normal washroom facilities.

#### Advice to Doctor

Treat symptomatically.

#### **Other Information**

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (131 126)

#### **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Carbon dioxide, dry chemical, foam, water spray.

### **Unsuitable Extinguishing Media**

Do not use water jet.

#### **Hazards from Combustion Products**

Under fire conditions this product may emit toxic and/or irritating fumes including oxides of nitrogen, carbon monoxide and carbon dioxide.

Specific Hazards Arising From The Chemical Combustible. This product will burn if exposed to fire.

Hazchem Code •3Z

**Decomposition Temperature** Not available

#### Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

# **6. ACCIDENTAL RELEASE MEASURES**

#### **Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

# 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood.

#### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

#### **Storage Regulations**

Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940 - 2017.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Occupational exposure limit values**

No exposure standards have been established for this material, however, the TWA exposure standards for refined mineral oil mist is 5 mg/m<sup>3</sup>. As with all chemicals, exposure should be kept to the lowest possible levels.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eighthour working day, for a five-day week.

Source: Safe Work Australia.

#### **Biological Limit Values**

No biological limits allocated.

#### **Appropriate Engineering Controls**

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

#### **Respiratory Protection**

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

#### **Eye Protection**

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/ face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

#### **Hand Protection**

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

#### **Body Protection**

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Liquid	Appearance	Liquid
Odour	Not available	Decomposition Temperature	Not available
Melting Point	Not available	Boiling Point	170 - 390°C (fuel, diesel)
Solubility in Water	Not available	рН	Not available
Vapour Pressure	<1 hPa (20°C) (fuel, diesel)	Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Partition Coefficient: n- octanol/water	3 - 6 (fuel, diesel)
Density	0.84g/cm <sup>3</sup> (15°C) (Typical) (fuel, diesel)	Flash Point	63°C (estimated)(fuel, diesel)
Flammability	Combustible	Auto-Ignition Temperature	>220°C (fuel, diesel)
Flammable Limits - Lower	1% (volume) (fuel, diesel)	Flammable Limits - Upper	6% volume) (fuel, diesel)
Kinematic Viscosity	2 - 4.5 cSt (40°C) (fuel, diesel)		

# **10. STABILITY AND REACTIVITY**

#### **Chemical Stability**

Stable under normal conditions of handling and storage.

# Reactivity and Stability

Reacts with incompatible materials.

#### **Conditions to Avoid**

Heat, direct sunlight, open flames or other sources of ignition.

# Incompatible materials

Strong oxidising agents.

#### **Hazardous Decomposition Products**

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon monoxide and carbon dioxide.

#### **Possibility of hazardous reactions** Not available

Hazardous Polymerization Not available

# **11. TOXICOLOGICAL INFORMATION**

#### **Toxicology Information**

No toxicity data available for this material.

#### Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting. May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

#### Inhalation

Harmful if inhaled. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system.

#### Skin

May be irritating to skin. The symptoms may include redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

#### Eye

May be irritating to eyes. The symptoms may include redness, itching and tearing.

#### **Respiratory sensitisation**

Not expected to be a respiratory sensitiser.

#### **Skin Sensitisation**

Not expected to be a skin sensitiser.

#### Germ cell mutagenicity

Not considered to be a mutagenic hazard.

#### Carcinogenicity

Suspected of causing cancer. Classified as a suspected human carcinogen.

Diesel fuel is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

#### Reproductive Toxicity

Not considered to be toxic to reproduction.

#### STOT-single exposure

Not expected to cause toxicity to a specific target organ.

**STOT-repeated exposure** Not expected to cause toxicity to a specific target organ.

#### **Aspiration Hazard**

May be fatal if swallowed and enters airways.

#### Other Information

This product contains an Ototoxic substance. Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

# **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

Toxic to aquatic life with long lasting effects.

**Persistence and degradability** Not available

Mobility

Not available

**Bioaccumulative Potential** Not available

Other Adverse Effects Not available

#### Environmental Protection

Do not discharge this material into waterways, drains and sewers.

# **13. DISPOSAL CONSIDERATIONS**

#### Disposal considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not cut, puncture or weld on or near containers. Containinated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected.

# **14. TRANSPORT INFORMATION**

#### **Transport Information**

Road and Rail Transport (ADG Code): This material is classified as Dangerous Goods Class 9 Miscellaneous Dangerous Goods Class 9: Miscellaneous substances Dangerous Goods are incompatible in a placard load with any of the following: Class 1: Explosives (when the class 9 substance is a fire risk substance) Division 5.1: Oxidising substances (when the class 9 substance is a fire risk substance) and Division 5.2: Organic peroxides (when the class 9 substance is a fire risk substance) Note: Special Provision AU01: Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in: packagings that do not incorporate a receptacle exceeding 500 kg(L); or IBCs Marine Transport (IMO/IMDG): Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. Class/Division: 9 UN No: 3082 Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Kerosene) (MARINE POLLUTANT) Packing Group: III EMS: F-A, S-F Special Provisions: 274 335 969

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. Class/Division: 9 UN No: 3082 Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Kerosene) Packing Group: III Packaging Instructions (passenger & cargo): 964 Packaging Instructions (cargo only): 964 Hazard Label: Miscellaneous Special Provisions: A97, A158, A197

**U.N. Number** 3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(Contains Fuel diesel)

Transport hazard class(es) 9 Packing Group III Hazchem Code • 3Z IERG Number 47

IMDG Marine pollutant Yes

Transport in Bulk Not available

Special Precautions for User Not available

# **15. REGULATORY INFORMATION**

#### **Regulatory information**

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). Exempted.

# **Poisons Schedule**

Not Scheduled

# **16. OTHER INFORMATION**

#### Date of preparation or last revision of SDS

SDS Reviewed: September 2019 Supersedes: September 2014

#### References

- Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

- Standard for the Uniform Scheduling of Medicines and Poisons.

- Australian Code for the Transport of Dangerous Goods by Road & Rail.

- Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

- Workplace exposure standards for airborne contaminants.
- Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).
- Globally Harmonised System of Classification and Labelling of Chemicals.
- Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

# **END OF SDS**

#### © Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.