

SAFETY DATA SHEET

UNLEADED + ETHANOL

Infosafe No.: LQ12A
ISSUED Date : 24/02/2022
ISSUED by: UNITED PETROLEUM PTY LTD

Section 1 - Identification

Product Identifier

UNLEADED + ETHANOL

Company Name

UNITED PETROLEUM PTY LTD

Address

600 Glenferrie Road Hawthorn
Vic 3122 AUSTRALIA

Telephone/Fax Number

Tel: (03)9413 1400
Fax: (03)9413 1401

Emergency Phone Number

1300 131 001

Recommended use of the chemical and restrictions on use

Fuel, Gasoline

Other Names

Name	Product Code
10% ETHANOL	
UNLEADED E10	
PLUS ULP	
E10 ULP	

Illicit Drug Precursors

This product contains a Category III: Illicit Drug Reagent/Essential Chemical in the Code of Practice for Supply Division into Illicit Drug Manufacture.

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Aspiration hazard: Category 1

Carcinogenicity: Category 1A

Eye damage/irritation: Category 2A

Flammable liquids: Category 1

Germ cell mutagenicity: Category 1B

Hazardous to the Aquatic Environment - Acute Hazard: Category 2

Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2

Reproductive toxicity: Category 1A

Skin corrosion/irritation: Category 2

Specific target organ toxicity (repeated exposure): Category 1

Specific target organ toxicity (single exposure): Category 3 (Narcotic)

Signal Word (s)

DANGER

Hazard Statement (s)

H224 Extremely flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H360 May damage fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)

Health hazard, Exclamation mark, Flame, Environment



Precautionary Statement – Prevention

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Precautionary Statement – Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam to extinguish.
P391 Collect spillage.

Precautionary Statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary Statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

Other Information

This product contains an Ototoxic substance.

Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 3 - Composition and Information on Ingredients

Ingredients

Name	CAS	Proportion
Gasoline	86290-81-5	>90 %
Toluene	108-88-3	<30 %
Ethanol	64-17-5	<10 %
Xylene	1330-20-7	<10 %
Benzene	71-43-2	<5 %
cumene	98-82-8	<5 %
Ethylbenzene	100-41-4	<5 %
n-hexane	110-54-3	<3 %
propylbenzene	103-65-1	<5 %
Trimethyl Benzene	25551-13-7	<5 %

Section 4 - First Aid Measures

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. This light hydrocarbon material, or a component, may be associated with cardiac sensitisation following very high exposures (well above occupational exposure limits) or with concurrent exposure to high stress levels or heart-stimulating substances like epinephrine. Administration of such substances should be avoided.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

Section 5 - Firefighting Measures

Suitable Extinguishing Media

Carbon dioxide, dry chemical or foam.

Unsuitable Extinguishing Media

Do not use water in a jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including sulphur oxides, aldehydes, carbon monoxide, incomplete combustion products, carbon dioxide and oxides of nitrogen.

Specific hazards arising from the chemical

Extremely flammable liquid and vapour. Keep containers and fire-exposed surfaces cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

3YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

Section 6 - Accidental Release Measures

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations.

If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Other Information

This material is a static accumulator.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values

Gasoline, low boiling point naphtha

TWA: 900 mg/m³

Note: Carc.1B

Ethanol
TWA: 1000 ppm, 1880 mg/m³

Benzene
TWA: 1 ppm, 3.2 mg/m³
Note: Carc.1A

Cumene
TWA: 25 ppm, 125 mg/m³
STEL: 75 ppm, 375 mg/m³
Note: Sk

Ethylbenzene
TWA: 100 ppm, 434 mg/m³
STEL: 125 ppm, 543 mg/m³

N-Hexane
TWA: 20 ppm, 72 mg/m³

Toluene
TWA: 50 ppm, 191 mg/m³
STEL: 150 ppm, 574 mg/m³
Note: Sk

Trimethyl benzene
TWA: 25 ppm, 123 mg/m³

Xylene
TWA: 80 ppm, 350 mg/m³
STEL: 150 ppm, 655 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Carc. 1B: Presumed to have carcinogenic potential for humans.

Carc. 1A: Known to have carcinogenic potential for humans

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

Source: Safe Work Australia

Biological Monitoring

Name: Benzene

Determinant: S-Phenylmercapturic acid in urine

Value: 25 µg/g creatinine

Sampling time: End of shift.

Notation: B

Determinant: t,t-Muconic acid in urine

Value: 500 µg/g creatinine

Sampling time: End of shift.

Notation: B

Name: Xylene

Determinant: Methylhippuric acids

Specimen: Creatinine in urine.

Value: 1.5g/g

Sampling time: End of shift.

Name: Ethylbenzene

Determinant: Sum of mandelic acid and phenylglyoxylic acid.
Specimen: Creatinine in urine.
Value: 0.15 g/g
Sampling time: End of shift at end of work week.

Name: n-hexane
Determinant: 2,5-Hexanedione in urine**
Value: 0.5 mg/l
Sampling time: End of shift.
**without hydrolysis

Name: Toluene
Determinant: Toluene in blood
Value: 0.02 mg/L
Sampling time: Prior to last shift of workweek

Determinant: Toluene in urine
Value: 0.03 mg/L
Sampling time: End of shift.

Determinant: o-Cresol in urine*
Value: 0.3 mg/g creatinine
Sampling time: End of shift.
* with hydrolysis

Source: American Conference of Industrial Hygienists (ACGIH)

Control Banding

Not available

Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye and Face Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as nitrile, viton. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Thermal Hazards

No further relevant information available.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Section 9 - Physical and Chemical Properties

Properties	Description	Properties	Description
Form	Liquid	Appearance	Liquid
Colour	Clear (May Be Dyed)	Odour	Petroleum/Solvent
Melting Point	Not available	Boiling Point	30 - 230°C
Decomposition Temperature	Not available	Solubility in Water	Moderate
Specific Gravity	Not available	pH	Not available
Vapour Pressure	30 kPa (225 mm Hg) at 20 °C - 100 kPa (750 mm Hg) at 20 °C	Relative Vapour Density (Air=1)	Not available
Evaporation Rate	>10 (n-butyl acetate=1)	Odour Threshold	Not available
Viscosity	<1 cSt (1 mm ² /s) at 40°C	Partition Coefficient: n-octanol/water (log value)	Not available
Density	0.735 (15°C)	Flash Point	< -40 °C (ASTM D-56)
Flammability	Extremely Flammable	Auto-Ignition Temperature	Not available
Flammable Limits - Lower	1.4% v/v	Flammable Limits - Upper	7.6% v/v
Particle Characteristics	Not applicable		

Section 10 - Stability and Reactivity

Chemical Stability

Stable under normal conditions of storage and handling.

Possibility of hazardous reactions

Not available

Conditions to Avoid

Heat, open flames and other sources of ignition.

Incompatible Materials

Halogens, strong acids, strong oxidising agents, alkalies.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: oxides of nitrogen, carbon dioxide and carbon monoxide.

Reactivity and Stability

Reacts with incompatible materials.

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information

Toxicology Information

Toxicity data for material given below.

Acute Toxicity - Oral

LD50(rat): > 5000 mg/kg

Acute Toxicity - Dermal

LD50(rat): > 5000 mg/kg

Acute Toxicity - Inhalation

LC50(rat): expected to be > 5 mg/m³

Ingestion

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

Inhalation

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Species: rabbit

Irritating to the skin. Based on test data for structurally similar materials.

Test(s) equivalent or similar to OECD Guideline 404.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Species: rabbit

May cause mild, short-lasting discomfort to eyes.

Based on test data for structurally similar materials.

Test(s) equivalent or similar to OECD Guideline 405.

Respiratory Sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ Cell Mutagenicity

May cause genetic defects. Classified as Known or presumed to induce heritable mutations.

Carcinogenicity

May cause cancer. Classified as a Known or presumed human carcinogen.

Benzene is listed as a Group 1: Carcinogenic to humans according to International Agency for Research on Cancer (IARC).

Ethylbenzene and Cumene are listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC).

Toluene and Xylene are listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

May damage fertility or the unborn child. Classified as a Known or presumed human reproductive or developmental toxicant.

STOT - Single Exposure

May cause drowsiness or dizziness.

STOT - Repeated Exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Other Information

BENZENE: Caused cancer (acute myeloid leukemia and myelodysplastic syndrome), damage to the blood-producing system, and serious blood disorders in human studies. Caused genetic effects and effects on the immune system in laboratory animal and some human studies. Caused toxicity to the fetus and cancer in laboratory animal studies.

CUMENE: Repeated inhalation exposure of cumene vapour produced damage in the kidney of male rats only. These effects are believed to be species specific and are not relevant to humans. **ETHANOL:** Prolonged or repeated exposure to high concentrations of ethanol vapour or overexposure by ingestion may produce adverse effects to brain, kidney, liver, and reproductive organs, birth defects in offspring, and developmental toxicity in offspring.

N-HEXANE: Prolonged and/or repeated exposures to n-Hexane can cause progressive and potentially irreversible damage to the peripheral nervous system (e.g. fingers, feet, arms, legs, etc.). Simultaneous exposure to Methyl Ethyl Ketone (MEK) or Methyl Isobutyl Ketone (MIBK) and n-Hexane can potentiate the risk of adverse effects from n-Hexane on the peripheral nervous system. n-Hexane has been shown to cause testicular damage at high doses in male rats. The relevance of this effect for humans is

unknown.

TOLUENE : Concentrated, prolonged or deliberate inhalation may cause brain and nervous system damage. Prolonged and repeated exposure of pregnant animals (> 1500 ppm) have been reported to cause adverse fetal developmental effects.

TRIMETHYLBENZENE: Long-term inhalation exposure of trimethylbenzene caused effects to the blood in laboratory animals.

ETHYLBENZENE: Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.

This product contains an Ototoxic substance. Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 12 - Ecological Information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Persistence and degradability

Expected to be inherently biodegradable. Expected to degrade rapidly in air

Mobility

Majority of components -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

Low molecular wt. component -- Moderate potential to migrate through soil.

High molecular wt. component -- Low potential to migrate through soil.

Bioaccumulative Potential

Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

Acute Toxicity - Fish

Acute toxicity

LL50(fish): 1 - 100 mg/l/96h: data for similar materials

Acute Toxicity - Daphnia

Acute toxicity

EL50(daphnia magna): 1 - 100 mg/l/48h: data for similar materials

Chronic toxicity

NOELR:(daphnia magna): 1 - 10 mg/l/21d: data for similar materials

Acute Toxicity - Algae

Acute toxicity

EL50(pseudokirchneriella subcapitata): 1 - 1000 mg/l/72h: data for similar materials

Chronic toxicity

NOELR(pseudokirchneriella subcapitata): 1 - 10 mg/l/72h: data for similar materials

Hazardous to the Ozone Layer

This product is not expected to deplete the ozone layer.

Section 13 - Disposal Considerations

Disposal Considerations

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not cut, puncture or weld on or near containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers.

Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected.

To minimise personal exposure to the chemical, refer to Section 8—Exposure controls and personal protection.

Section 14 - Transport Information

Transport Information

Road and Rail Transport (ADG Code):

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1, Explosives
- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising Agents and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7: Radioactive materials unless specifically exempted

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 3

UN No: 1203

Proper Shipping Name: PETROL (MARINE POLLUTANT)

Packing Group: II

EMS : F-E, S-E

Special Provisions: 243

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 3

UN No: 1203

Proper Shipping Name: Petrol

Packing Group: II

Packaging Instructions (passenger & cargo): 353

Packaging Instructions (cargo only): 364

Hazard Label: Flammable Liquid

Special Provisions: A100

ADG U.N. Number

1203

ADG Proper Shipping Name

PETROL

ADG Transport Hazard Class

3

ADG Packing Group

II

Hazchem Code

3YE

IERG Number

14

Special Precautions for User

Not available

IMDG Marine pollutant

Yes

Transport in Bulk

Not available

Section 15 - Regulatory Information

Regulatory Information

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

S5

Australia (AICS/AIIC)

All components of this product are listed on the Inventory or exempted.

Montreal Protocol

Not listed

Stockholm Convention

Not available

Rotterdam Convention

Not available

International Convention for the Prevention of Pollution from Ships (MARPOL)

Not available

Agricultural and Veterinary Chemicals Act 1994

Not available

Basel Convention

Not available

Section 16 - Any Other Relevant Information

Date of Preparation

SDS reviewed: February 2022, Supersedes: February 2017

Version Number

Version 3.0

Literature References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Code of Practice for Supply Diversion into Illicit Drug Manufacture.

National Code of Practice for Chemicals of Security Concern.

Agricultural Compounds and Veterinary Chemicals Act.

International Agency for Research on Cancer (IARC) Monographs.

Montreal Protocol on Substances that Deplete the Ozone Layer.

Stockholm Convention on Persistent Organic Pollutants (POPs).

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.

International Air Transport Association (IATA) Dangerous Goods Regulations.

International Maritime Dangerous Goods (IMDG) Code.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals. (7th revised edition)

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical

Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.