

SAFETY DATA SHEET

E85

Infosafe No.: LQ2ZX
ISSUED Date : 24/02/2022
ISSUED by: UNITED PETROLEUM PTY LTD

Section 1 - Identification

Product Identifier

E85

Company Name

UNITED PETROLEUM PTY LTD

Address

600 Glenferrie Road Hawthorn
Vic 3122 AUSTRALIA

Telephone/Fax Number

Tel: (03)9413 1400

Fax: (03)9413 1401

Emergency Phone Number

1300 131 001

Recommended use of the chemical and restrictions on use

Ethanol based fuel.

Other Names

Name	Product Code
ETHANOL 85	
85% ETHANOL + 15% PULP	
85% ETHANOL + 15% ULP98	
85% ETHANOL + 15% PREMIUM UNLEADED PETROL	

Illicit Drug Precursors

This product contains a Category III: Illicit Drug Reagent/Essential Chemical in the Code of Practice for Supply Division into Illicit Drug Manufacture.

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Acute toxicity: Category 4 - Dermal

Acute toxicity: Category 4 - Inhalation

Acute toxicity: Category 4 - Oral

Aspiration hazard: Category 1

Carcinogenicity: Category 1B

Eye damage/irritation: Category 2A

Flammable liquids: Category 2

Germ cell mutagenicity: Category 1B

Skin corrosion/irritation: Category 2

Signal Word (s)

DANGER

Hazard Statement (s)

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H340 May cause genetic defects.

H350 May cause cancer.

Pictogram (s)

Exclamation mark, Health hazard, Flame

**Precautionary Statement – Prevention**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Precautionary Statement – Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam. (Alcohol resistant foam is preferred. If not available normal foam can be used.) to extinguish.

Precautionary Statement – Storage

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

Other Information

This product contains an Ototoxic substance.

Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 3 - Composition and Information on Ingredients

Ingredients

Name	CAS	Proportion
Ethanol	64-17-5	85 %
Premium unleaded petrol (PULP98)		15 %
Additives		Trace

Section 4 - First Aid Measures

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

Section 5 - Firefighting Measures

Suitable Extinguishing Media

Carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific hazards arising from the chemical

Highly flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

•3YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

Section 6 - Accidental Release Measures

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations.

If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Ethanol

TWA: 1000 ppm, 1880 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Source: Safe Work Australia

Biological Monitoring

No biological limits allocated.

Control Banding

Not available

Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye and Face Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as PVC or neoprene. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Thermal Hazards

No further relevant information available.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Section 9 - Physical and Chemical Properties

Properties	Description	Properties	Description
Form	Liquid	Appearance	Clear - pale yellow liquid
Colour	Clear - pale yellow	Odour	Characteristic fuel odour
Melting Point	-117°C (Ethanol)	Boiling Point	78°C (Ethanol) 25-228°C (Unleaded petrol)
Decomposition Temperature	Not available	Solubility in Water	Complete (Ethanol) Negligible (Unleaded petrol)
Specific Gravity	0.79-0.81 (Ethanol) 0.73 (approximate)(Unleaded petrol)	pH	Not available
Vapour Pressure	44mmHg (20°C) (Ethanol) 35-90kPa (Unleaded petrol)	Relative Vapour Density (Air=1)	1.59 (Ethanol) 3.5 (Unleaded petrol)
Evaporation Rate	253 (Ethanol) (n-Butyl acetate=100)	Odour Threshold	Not available
Viscosity	Not available	Volatile Component	100%
Partition Coefficient: n-octanol/water (log value)	Not available	Flash Point	13°C (Ethanol) -40°C (Unleaded petrol) Method: Abel closed cup
Flammability	Highly flammable	Auto-Ignition Temperature	392°C (Ethanol) >250°C (Unleaded petrol)
Flammable Limits - Lower	3.5% (Ethanol) 1% (Unleaded petrol)	Flammable Limits - Upper	19% (Ethanol) 8% (Unleaded petrol)
Particle Characteristics	Not applicable		

Section 10 - Stability and Reactivity

Chemical Stability

Stable under normal conditions of storage and handling.

Possibility of hazardous reactions

Not available

Conditions to Avoid

Heat, open flames and other sources of ignition.

Incompatible Materials

Incompatible with oxidising agents (eg. Hypochlorites, peroxides), acids (sulphuric acid), strong alkalis (eg. Hydroxides).

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes and gases including oxides of nitrogen, carbon monoxide and carbon dioxide.

Reactivity and Stability

Reacts with incompatible materials

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information

Toxicology Information

The available acute toxicity data is given below.

Acute Toxicity - Oral

LD50 (rat): 7060 mg/kg (literature)

Acute Toxicity - Inhalation

LC50 (rat): 38 mg/l/10h (literature)

Ingestion

Harmful if swallowed. May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

Swallowing ethanol can cause drunkenness or harmful central nervous system effects. The deliberate ingestion of ethanol is a known occupational risk.

As little as 50 - 100 ml intake in a shift in a 70kg worker may cause inebriation to the point where safety is impaired. Effects of a small intake may include excitation, euphoria, headache, dizziness, drowsiness, blurred vision, and fatigue. Drinking a large amount may lead to severe acute intoxication, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death.

Inhalation

Harmful if inhaled. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system.

Skin

Harmful in contact with skin. Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory Sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ Cell Mutagenicity

May cause genetic defects. Classified as Known or presumed to induce heritable mutations.

Carcinogenicity

May cause cancer. Classified as a Known or presumed human carcinogen.

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT - Single Exposure

Not expected to cause toxicity to a specific target organ.

STOT - Repeated Exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

May be fatal if swallowed and enters airways.

Other Information

This product contains an Ototoxic substance.

Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 12 - Ecological Information

Ecotoxicity

The available ecological data is given below.

Persistence and degradability

Ethanol:

Biodegradable, 94% elimination

Mobility

See section 12 Persistence/ Degradability

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Do not discharge this material into waterways, drains and sewers.

Acute Toxicity - Fish

Ethanol:

LC0 (Golden ide): >1000mg/l/48h

Acute Toxicity - Daphnia

Ethanol:

EC50 (Daphnia magna) : >1000mg/l/24h

Hazardous to the Ozone Layer

This product is not expected to deplete the ozone layer.

Section 13 - Disposal Considerations

Disposal Considerations

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. To minimise personal exposure to the chemical, refer to Section 8—Exposure controls and personal protection.

Section 14 - Transport Information

Transport Information

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN-No: 3475

Proper Shipping Name: ETHANOL AND PETROL MIXTURE

Class: 3

Packaging Group: II

EMS No.: F-E, S-E

Special Provisions: 333, 363

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN-No: 3475
Proper Shipping Name: ETHANOL AND PETROL MIXTURE
Class: 3
Packaging Group: II
Label: Flammable Liquid
Packaging Instructions (passenger & cargo): 353
Packaging Instructions (cargo only): 364
Special Provision: A156

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1: Explosives
- Division 2.1: Flammable Gases.
(Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L)
- Division 2.3: Toxic Gases
- Division 4.2: Spontaneously Combustible Substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic Peroxides
- Class 6: Toxic or Infectious Substances
(where the flammable liquid is nitromethane)
- Class 7: Radioactive materials unless specifically exempted.

ADG U.N. Number

3475

ADG Proper Shipping Name

ETHANOL AND PETROL MIXTURE

ADG Transport Hazard Class

3

ADG Packing Group

II

Hazchem Code

•3YE

IERG Number

14

Special Precautions for User

Not available

IMDG Marine pollutant

No

Transport in Bulk

Not available

Section 15 - Regulatory Information

Regulatory Information

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of chemicals (GHS) including Work, Health and Safety regulations, Australia.

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

Not Scheduled

Australia (AICS/AIIC)

All components of this product are listed on the Inventory or exempted.

Montreal Protocol

Not listed

Stockholm Convention

Not listed

Rotterdam Convention

Not listed

International Convention for the Prevention of Pollution from Ships (MARPOL)

Not available

Agricultural and Veterinary Chemicals Act 1994

Not available

Basel Convention

Not available

Section 16 - Any Other Relevant Information

Date of Preparation

SDS reviewed: February 2022 Supersedes: February 2017

Version Number

3.0

Literature References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Code of Practice for Supply Diversion into Illicit Drug Manufacture.

National Code of Practice for Chemicals of Security Concern.

Agricultural Compounds and Veterinary Chemicals Act.

International Agency for Research on Cancer (IARC) Monographs.

Montreal Protocol on Substances that Deplete the Ozone Layer.

Stockholm Convention on Persistent Organic Pollutants (POPs).

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.

International Air Transport Association (IATA) Dangerous Goods Regulations.

International Maritime Dangerous Goods (IMDG) Code.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals (7th revised edition).

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.